

# CabLite ECO

## SPECIFICATIONS

### Model: CabLite<sup>®</sup>ECO



**Material** Stamped Aluminum

**Mounting** High Tensile Spring Fasteners

<b>Dimensions</b>	(Raised Bezel)	(Flat Bezel)
	2.00" Height Overall	2.00" Height Overall
	2.75" Hole Cutout	3.125" Hole Cutout
	3.00" Overall Diameter	3.75" Overall Diameter

### Finishes (Standard)

	Black	Black
	Silver	Silver
	#4 Brushed Stainless	#4 Brushed Stainless
(optional colors)	White, Gold, Bronze	White, Gold, Bronze

### LED

Viewing Angle	120 Degree	120 Degree	120 Degree
Kelvin Temperature	3000K	4000K	5000K
CRI	82.9	84.6	85.3
Lumens	228.58 lm	261.24 lm	320.68 lm
Number LED	9	9	9
Wattage	5	5	5
Input Voltage	24VDC	24VDC	24VDC

\*Note: Lumen calculations based on Independant Laboratory Testing.

**Power Supply** Input 100VAC– 240VAC 50/60Hz for Worldwide installation  
Output : +24VDC

**Dimming Control** 30...100% (Included)  
Dimming Control Secondary Remote for COP (optional)

### Hardware & Wiring

Includes electrical box with plug & play quick connect wiring harness cables.

**Emergency Lighting** - Battery Back Up (Optional)  
Operates two lights and exceeds elevator code requirements through AMSE 17.3 -2010

**Fixture Covers** (Optional) for top of car through canopy installations with conduit knock outs.